CRYSTEPO

- CRYSTEPO V
- CRYSTEPO 3
- CRYSTEPO 5

CE marking:
→ CRYSTEPO 3 • EN 13813 • Designation: SR-B2,0-AR0,5-IR4
→ CRYSTEPO V • EN 1504-2 (C) • Principles: MC-IR
→ CRYSTEPO 50 • EN 13813 • Designation: SR-B3,5-AR0,5-IR4

TECHNICAL FEATURES

WATERPROOF

EFI

STAIN RESISTANT

SLOW CURING

FIELD OF APPLICATION

INTERIORS

INT. FLOORS

APPLICATIONS



2 PART

TROWEL

WALKABLE

Consumption

type of application	minimum consumption	maximum consumption	u.m.	notes
CRYSTEPO 3 ► To make a product coat between 2 and 3 mm thick.	2,2	3,3	kg/m²	(1)
CRYSTEPO 50 C Realization of casting products (resin mass (A + B) for L of hardened casting).	1,05	1,10	kg/L	-
CRYSTEPO V C By hand of applied product.	0,10	0,12	kg/m²	(2)

(1) To achieve a hardened product thickness of approx. 1 mm, 1.08 kg/m² of mixture A+B must be applied.
(2) At 0.10 - 0.12 kg/m², a final thickness of approx. 90 - 100 microns is achieved.

Technical Data

► PRODUCT IDENTIFICATION DATA	value
0	

Packaging

VARIANT	PACKAGE	ADR	PACKAGE / PALLET	COMPONENTS	NOTE
CRYSTEPO 3	kit (A+B) - 7.25 kg	P*	21 kit	A = 4,75 kg (steel bucket) B = 2.5 kg (jerry can)	-
CRYSTEPO 50	kit (A+B) - 4.4 kg	P*	-	A = 3.4 kg (steel bucket) B = 1.0 kg (tin can)	-
CRYSTEPO V	kit (A+2B) - 6.0 kg	P*	36 kits	A = 4,0 kg (metal drum) B = 2 x 1 kg (PP jar)	-

ADR legend:
NO = NON-DANGEROUS goods
P* = DANGEROUS goods packed in limited quantities (packed as per ADR Chapter 3.4)
SI = DANGEROUS Goods

VIA FORNACE VECCHIA, 79
31058 SUSEGANA (TV) - Italy
Tel +39 0438 437511
www.resinenativus.it

CRYSTEPO

LEGAL NOTES

Any advice concerning the methods of use of our products reflects the current state of knowledge and does not imply any guarantee and/or responsibility as to the outcome of the application. Consequently, the customer must verify the product's suitability for the intended use and purposes by testing the product in advance. The Internet website www.resinenativus.it contains the latest revision of this technical sheet: in case of any doubts, verify the date of revision (where missing, use the date of issue) by consulting the "Download → Technical data sheet" section.

VIA FORNACE VECCHIA, 79
31058 SUSEGANA (TV) - Italy
Tel +39 0438 437511

www.resinenativus.it